

MYLANDS

MASONRY PAINT FOR EXTERIOR USE

PRODUCT NAME	CODE	SHEEN LEVEL
Masonry Paint (Pure White)	50 745 0001	5%

PRODUCT DETAILS

A waterbased acrylic for use on masonry.

NOT suitable over limewash or lime based renders.

APPLICATION

- ◆ Ensure all surfaces are clean, dry and free of contamination.
- ◆ If painting over powdery or porous surfaces use stabilising solution.
- ◆ Treat algal/fungal contaminated surfaces with dilute bleach or with a proprietary wash.
- ◆ Do not use in extremes of temperature.
- ◆ Use between 8°C and 30°C.
- ◆ Do not apply if there is likelihood of rain.

THINNING

If necessary to thin, water should be used **up to 10%**.

HEALTH & SAFETY

Refer to Mylands MSDS before use.

PRODUCT BENEFITS



Excellent coverage properties



Fast drying

two coats can be applied in one day.



Washable



Low odour



Excellent stain and chemical resistance

COVERAGE

On average per litre **15m²** dependant on substrate texture and porosity.

DRYING TIME



Touch dry in
1-2 hours.



Recoat in
4 hours.

CLEANING

Wash brushes/rollers immediately after use, in warm water containing a little detergent.

STORAGE

This product must be protected from frost. Store at temperature above 5°C.

Use within 18 months.



+5°C

SIZES AVAILABLE



For further information
visit our website: www.mylands.com
or contact us: +44 (0)208 670 9161
sales@mylands.com



By Appointment to Her Majesty Queen Elizabeth II
Manufacturers of French Polishes, Stains and Wax Polishes
John Myland Limited, London

Last updated 09.02.2022