MYLANDS

PRO-TRADE MATT EMULSION PAINT

FOR INTERIOR USE

PRODUCT NAME

CODE

SHEEN LEVEL

Pro-Trade Matt Emulsion

50 301 0001

5%

PRODUCT DETAILS

With its full density, low sheen, and hard-wearing finish, Mylands Pro-Trade Matt Emulsion is a paint that delivers excellent value for money. Suitable for interior walls and ceilings. Water-based & environmentally friendly with low VOCs. Formulated with expert craftsmanship to deliver exceptional coverage, durability, and depth of colour. Available in all colours, 5% sheen. EN13300 class 1, certified class 1 European standards scrub test.

APPLICATION

- Before use clean surfaces to be painted ensuring any grease, dirt or flakes are removed.
- Do not use in extremes of temperature.
- Use between 8°C and 30°C.
- Stir well before use.
- This product is formulated for brush or roller and spray application.
- Use over appropriate wall primer if required.

THINNING

This paint has a high pigmentation and can be diluted with water when necessary.

On porous surfaces (e.g. bare plaster) Apply Mylands Pro-Trade Wall Primer, or Pro-Trade Matt Emulsion diluted 45% on the first coat. Pro-Trade Matt Emulsion diluted up to 10% on the second coat

On already painted walls Apply Pro-Trade Matt Emulsion diluted 10%

HEALTH & SAFETY

Refer to Mylands MSDS before use.

PRODUCT BENEFITS



Excellent coverage properties



Fast drying

two coats can be applied in one day.



Environmentally friendly



Washable



Low odour

COVERAGE PER COAT

Average coverage per: 1 Litre Tin 15m² 162 ft²

2.5 Litre Tin 37.5m² 405 ft²

2 coats recommended 5 Litre Tin 75 m² 810 ft²

DRYING TIME



Touch dry in 1-2 hours.



Recoat in **3-4 hours.**

CLEANING

Wash brushes/rollers immediately after use, in warm water containing a little detergent.

STORAGE

This product must be protected from frost. Store at temperature above 5° C// 41° F.



Use within 18 months.

+5°C/41°F

SIZES AVAILABLE





